

testo 440 delta P flow ComboKit 1 with Bluetooth®

Kit for measurement in ducts,
at outlets and on filters

Structured, intuitive measurement menus for volume flow

Parallel measurement of flow, differential pressure, humidity
and temperature

Universal Bluetooth® handle for different wireless probe
heads

Internal data storage and USB port for data export

Integrated differential pressure sensor and a large portfolio
of digital probes



Compatible with a wide
selection of Bluetooth® and
wired probes.

With the testo 440 delta P flow ComboKit 1 with Bluetooth®, all IAQ-related parameters at air vents, in ducts and at filters can be measured and documented wirelessly. The air velocity & IAQ measuring instrument recognizes probes automatically, and its structured measurement menus simplify the adjustment of air conditioning and ventilation systems. In addition to a Bluetooth® probe, a wired probe and a thermocouple Type K temperature probe can also be connected to the measuring instrument.

The versatile Bluetooth® handle allows the connection of many different wireless probe heads for all applications. The kit also contains a vane probe head, a hot wire probe head, an extendable telescope for flow velocity probes and a storage case.




Scope of delivery

- testo 440 dP air velocity & IAQ measuring instrument, incl. differential pressure sensor, connection hose, 3x AA batteries, USB cable and calibration protocol (0560 4402)
- Vane probe (Ø 100 mm) with Bluetooth® incl. temperature sensor (consisting of 100 mm vane probe head, handle adapter and Bluetooth® handle); bracket for testovent measurement funnel; 4x AA batteries and calibration protocol (0635 9431)
- Hot wire probe head (Ø 9 mm) including temperature and humidity sensor and calibration protocol (0635 1570)
- Extendable telescope (length up to 1 m) for flow probes with a universal handle including 90° angle (0554 0960)
- Combi-case for testo 440 and multiple probes (0516 4401)



Order no. 0563 4409


1981 0624/msp/1/04_2019

Technical data	Measuring range	Accuracy	Resolution
Digital probes			
Vane probe (Ø 100 mm) with Bluetooth® , including temperature sensor 	0.3 to 35 m/s -20 to +70 °C	±(0.1 m/s + 1.5 % of m.v.) (0.3 to 20 m/s) ±(0.2 m/s + 1.5 % of m.v.) (20.1 to 35 m/s) ±0.5 °C	0.01 m/s 0.1 °C
Hot wire probe head (Ø 9 mm) incl. temperature and humidity sensor 	0 to 50 m/s -20 to +70 °C 5 to 95 %RH 700 to 1100 hPa	±(0.03 m/s + 4 % of m.v.) (0 to 20 m/s) ±(0.5 m/s + 5 % of m.v.) (20.01 to 30 m/s) ±0.5 °C (0 to +70 °C) ±0.8 °C (-20 to 0 °C) ±3.0 %RH (10 to 35 %RH) ²⁾ ±2.0 %RH (35 to 65 %RH) ²⁾ ±3.0 %RH (65 to 90 %RH) ²⁾ ±5 %RH (remaining meas. range) ²⁾ ±3 hPa	0.01 m/s 0.1 °C 0.1 %RH 0.1 hPa
testo 440 dP			
testo 440 dP air velocity & IAQ measuring instrument Connectable probes: 1x digital probe with cable or 1x temperature NTC TUC, 1x digital Bluetooth® probe or Testo Smart Probes, 1x differential pressure (internal), 1x temperature TC Type K 	Differential pressure -150 to +150 hPa		±0.05 hPa (0 to +1.00 hPa) ±0.2 hPa + 1.5 % of m.v. (+1.01 to +150 hPa) 0.01 hPa

¹⁾ For use with Bluetooth® handle and adapter included in delivery or with the wired handle (order no. 0554 2222).
²⁾ Please see the additional accuracy information for humidity in the instruction manual.

General technical data	testo 440	Vane probe (Ø 100 mm) with Bluetooth®	Hot wire probe head (Ø 9 mm)	Extendable telescope
Data transmission	Bluetooth®, USB interface	Bluetooth®, Wireless range up to 20 m		
Operating temperature	-20 to +50 °C	-20 to +70 °C	-20 to +70 °C	-5 to +50 °C
Storage temperature	-20 to +50 °C	-20 to +70 °C	-20 to +70 °C	-20 to +60 °C
Dimensions	154 x 65 x 32 mm	375 x 105 x 46 mm	235 x 12 x 12 mm	Telescope: 375 x 17 x 16 mm Angle: 65 x 65 x 15 mm
Probe head diameter		Ø 100 mm	Ø 9 mm	Ø 12 mm
Weight	250 g	360 g	35 g	155 g

You will find the complete selection of probes and accessories for the testo 440 in the testo 440 data sheet or at www.testo.com.



Subject to change, including technical modifications.